

SMP10

Power Supply/Charger

Description

Altronix SMP10 power supply/charger converts a low voltage AC input into a 12VDC or 24VDC output. This unit has a wide range of applications for access control, security, and CCTV system accessories that require additional power.



SMP10

Specifications

Input

Voltage 24VAC or 28VAC.

Outputs

| Output Voltage/Current | Required Input Voltage | Altronix Transformer |
|------------------------|------------------------|----------------------|
| 12VDC @ 10A | 24VAC or 28VAC / 175VA | T2428175 |
| 24VDC @ 6A | 28VAC / 175VA | T2428175 |
| 24VDC @ 10A | 28VAC / 300VA | T2428300 |

Other Short circuit and thermal overload protection. Filtered and regulated.

Back-up Battery *(not included)*

Type Sealed lead acid or gel type.
Failover Upon AC loss, instantaneous.

Indicators (LED)

Input Input voltage is present.
DC Output Powered.

Physical and Environmental

Dimensions (L x W x H)

7" x 4.25" x 1.25" (177.8mm x 107.9mm x 31.8mm).

Product Weight 0.55 lbs. (0.25 kg).

Shipping Weight 0.7 lbs. (0.32 kg).

Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr (approx.):

12VDC: 61 BTU/Hr.
24VDC: 123 BTU/Hr.

Mounting hardware included.

SMP10

Power Supply/Charger

Board Dimensions (L x W x H) and Drawing

7" x 4.25" x 1.25" (177.8mm x 107.9mm x 31.8mm)

