# **MAGIC SWITCH: MS11**

# ADJUSTABLE RANGE, STAINLESS STEEL TOUCHLESS ACTUATOR






























# DESCRIPTION

BEA's MS11 is an aesthetically pleasing, touchless activation device designed to reduce the spread of germs and improve accessibility in healthcare, retail, industrial and commercial settings. The MS11 has been purpose-built to withstand the extreme rigors of fast-paced and sanitary environments.

The flush-mount MS11 is a durable stainless steel device utilizing adjustable-range microwave technology. The MS11's illuminated center and audible signaling confirms activation and encourages proper touchless use.

The MS11 detects moving objects such as a hand, cart or wheelchair and is designed for use in hospitals, pharmacies, clean rooms, food service and other areas needing highly accessible and germ-free activation.

## FEATURES & BENEFITS

- NEMA 4 (IP65) enclosure capable of use in industrial and extreme washdown environments
- Illuminated blue center changes to green upon signal reception/activation
- Adjustable sensing zone from 2 to 24 inches (pulse or toggle)
- Adjustable audible alert setting, including silent-mode required for hospitals and other noise-sensitive environments
- Configurable output hold time of 1 to 30 seconds allowing unique, user-defined device placement
- Inter-operates with all automatic door control makes and models



BEA, Inc. **RIDC Park West** 100 Enterprise Drive

Customer Service: 800.523.2462 Technical Support: 800.407.4545

Pittsburgh, PA 15275-1213 www.BEAinc.com

#### APPLICATIONS








#### TECHNICAL SPECIFICATIONS

Technology	Microwave Doppler Radar
Detection Mode	Motion (bidirectional), Toggle or Timed Mode
Sensing Zone **	2 to 24 inches (adjustable)
Hold Time	1 to 30 s
Alert Settings	
Audible Alert	Silent Mode or Signal Mode
Visual Alert	Blue (Standby) Green (Activation)
Supply Voltage	12-24 V AC/DC or +5 VDC
Current Consumption	< 2.8W
Temperature Range	-22° F to 158° F
Enclosure Rating	NEMA 4 / IP65
Delev	1-Form C Solid State Relay
Relay	1A 30VAC/VDC (max)
	Single Gang: 4.5 in × 2.75 in × 0.98 in
Dimensions (Overall)	Double Gang: 4.5 in x 4.5 in x 0.98 in
	Jamb: 4.5 in × 1.68 in × 0.98 in
Wire Harness Length	12 inches
Material	Stainless Steel (faceplate)/ ABS (center)

## DIMENSIONAL DRAWINGS

\*\* See User's Guide



#### PRODUCT FAMILY



10MS11S STAINLESS STEEL SINGLE GANG



STAINLESS STEEL JAMB STYLE



10MS11D STAINLESS STEEL DOUBLE GANG

# RELATED PRODUCTS



MS08 SERIES STANDARD **MICROWAVE** ACTUATOR



MS09 SERIES INDUSTRIAL **MICROWAVE** ACTUATOR



**MS21H SERIES** SHORT-RANGE STAINLESS STEEL ACTUATOR



900 MHZ WIRELESS **TRANSMITTERS** AND RECEIVERS

Customer Service: 800.523.2462

www.BEAinc.com © 2016 BEA, Inc. All rights reserved.

79.0200.11

MAGIC SWITCH: MS11 ADJUSTABLE RANGE, STAINLESS STEEL TOUCHLESS ACTUATOR



