TECH-SPEC:

Product Reference Sheet

2748_

Example: 2748 | A | 36

/ | | | Profile# Finish Length

CATEGORY: Commercial Thresholds

TYPE: Saddle Thresholds

FINISHES: A (Mill Finish), D (Dark Anodized), G (Gold Anodized)

LENGTHS: Up to 185"

WIDTH: 8" (203.2 mm)

HEIGHT: 1/4" (6.35 mm)

WEIGHT: Estimated per foot: 1.3 lbs

RATINGS:



BHMA

PRODUCT APPROVALS:

- Tested and approved under ULIOC for Fire
- ADAAG-1998 (Amended); ICC/ANSI A117.1 and California Building Code, Title 24 for Barrier-Free Entry
- Category J gaskets for use with listed steel frames and/or classified steel covered composite, hollow metal doors rated up to and including 3 hours; wood and plastic covered composite doors rated up to and including 1-1/2 hours; and wood core doors rated for 20 minutes.

PROFILE DRAWING

ANSI NUMBER: Aluminim: J32100, J32130

LEAD TIME: 4 working days (or less)

AVAILABLE: Shipped from PEMKO's Memphis, Ventura, Vancouver and Toronto locations

CROSS REFERENCE: Draftseal: DS8000; Hager 428S; NGP: 813; Reese: S408; Zero: 548A;

K N Crowder: CT-68

INSTRUCTIONS: Available upon request and on website

CAD DRAWINGS: Available upon request and on website

PROFILE DRAWINGS: Available upon request and on website

CUT SHEET: Available upon request and on website

www.pemko.com

Memphis, TN USA Ventura, CA USA Vancouver, BC Canada Toronto, ON Canada P.O. Box 18966 P.O. Box 3780 103-2480 Mt. Lehman Rd. 160 Four Valley Dr. Memphis.TN 3818 Ventura, CA 93006 Abbotsford, BC V2T 6W3 Vaughan, ON L4K 4T9 P: 800.283.9988 P: 877.535.7888 P: 877.535.7888 P: 800.824.3018 F: 800.283.4050 F: 877.535.7444 F: 877.535.7444 F: 800.243.3656

