



RB1224

Relay Module

Altronix RB1224 Relay Module can be utilized in many different applications such as: Dry Contact, Line Seizure, Polarity Reversal, Latching Dry Contact, and much more. RB1224 is Snap Track mountable.



-25°C to 55°C (-13°F to 131°F)

-25°C to 70°C (-13°F to 158°F)

RB1224

| C. | | \sim | | | 0 | •. | | - | |
|-----------------|--------|--------|---------------------------------|-------|---|----|---------------|---|---|
| S | | _ | | | ~ | | () | | - |
| $\mathbf{\sim}$ | \sim | v | $\mathbf{\mathbf{\mathcal{I}}}$ | • | u | ٠. | $\overline{}$ | | v |
| | | | | | | | | | |

Input
Voltage

12VDC or 24VDC operation

Physical and Environmental
Dimensions (L x W x H)

Current Draw 75mA 2.75" x 2" x 1" (69.85mm x 50.08mm x 25.4mm)

Product Weight 0.15 lb. (0.06 kg)

Contact Rating 5A/220VAC or 28VDC DPDT contacts Shipping Weight 0.25 lb. (0.11 kg)

Indicators (LED) Temperature Operating

Trigger Relay is triggered Storage

Remote LED status output Relative Humidity 85% +/-5%