

PowerMatic®  
Low Energy Operator:

**6000** *series*

Intelligent, Reliable Control



**Norton®**  
**ASSA ABLOY**

ASSA ABLOY, the global leader  
in door opening solutions

## 6000 Series Low Energy Operator



Part of the PowerMatic® Series of low energy operators, the 6000 provides intelligent and superior door control for high usage, heavy duty applications. A full featured unit, the 6000 offers built-in intelligence like Push and Go and Obstruction Detection to meet the needs of your facility.

### Benefits

#### Easy Installation, Commissioning and Maintenance

- Modular construction for easy, one person installation
- LCD screen and joystick controller ease setup without special tools or training
- Configurable to meet virtually any site, activation or system integration requirements

#### Flexible

- Large onboard power supply to handle multiple system peripherals
- Coordinates with smoke evacuation "blow-open" requirements

#### Reliable and Durable Operation

- Uses Grade 1 7500 Series heavy duty door closer
- Interfaces with electric hardware and integrates with access control
- Operates as a mechanical surface closer when power is off

#### Built-in Intelligence

- Push and Go opens door to full-open position upon manual activation
- Obstruction Detection on both open and close cycle
- On board electronics collect usage and cycle count data to facilitate preventative maintenance/diagnostics

Norton Door Controls  
3000 Highway 74 East • Monroe, NC 28112  
Tel: 1-877-974-2255 • Fax: 1-800-338-0965

Norton® and PowerMatic® are trademarks of Yale Security Inc., an ASSA ABLOY Group company. These materials are protected under U.S. copyright laws. All contents current at time of publication. Copyright © 2012–2015, Yale Security Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Yale Security Inc. is prohibited.

### Features

- Push or pull side mounting
- Non-handed
- 1.3A onboard power supply
- Activated by push button, hands-free, and RF devices
- Infinite hold open
- Maximum door size 4'0" x 8'0", 250 lbs
- For use on fire-rated doors
- Meets ADA requirements

### Applications

- Government Buildings
- Convention Centers
- Hospitals
  - Examination Rooms
  - Main Entrance Doors
- Colleges or Universities
  - Entrance Doors
  - Gymnasium Doors
  - Common Areas
  - Dormitory Entrances

43251 5/15R